

SPACER SPOOLS

API 6A & 16A

DESIGN/APPLICATION:

- Fabritech MS, Inc. manufactures Spacer Spools in all sizes and pressure ratings suitable for Well Head extension, B.O.P. spacing, and Choke, Kill, and Production Manifold applications. API 16A configuration is for Drill Through operations, while API 6A configurations are not.

KEY FEATURES:

- Can be any overall length (OAL) as needed by customer or end user.
- Available in any size and pressure combination.
- Designed for working with H₂S (Sour Gas Service) and material complies with API 16A 4th Ed., API 6A 21st Ed., MR 0175 requirements, as well as API 16A 4th Ed. and API 6A 21st Ed. Temperature rating requirements. Ring grooves can be regular steel, or CRA (Inconel®).
- Pad eyes/ Lifting eyes and or outlets are not standard on Spacer Spools, but may be added upon request.

SPECS:

- Working pressure(s): 2,000 PSI – 20,000 PSI
- Size: 1-13/16", 2-1/16", 2-9/16", 3-1/8", 3-1/16", 4-1/16", 5-1/8", 7-1/16", 9", 11", 13-5/8", 16-3/4", 18-3/4", 20-3/4", 21-1/4", 26-3/4", 30".
- Ask your sales representative for clarification of size limitations for API 16A requirements.
- Medium: Natural Gas, Mud, and Oil.
- Working Temperature: -75° F - 250° F (-59° C - 121° C) API 16A 4th Ed. and -46° C-121° C for API 6A 21st Ed.
- Specification Class: PSL-1 through PSL-4 (API 6A)
- Performance Class: PR1
- Monogramable to API 16A or API 6A



Spacer Spools are depicted in the above renders. Customers have the ultimate responsibility of determining if the spool will be for drill through or wellhead purposes. Ask your sales representative for more information.